


StudioQuake **SERIES**

Powered Studio Monitors

The Sound That Will Move You





	StudioQuake M6	StudioQuake M8
(H) Height w/ feet	12-3/4" (324mm)	15-1/8" (384mm)
(W) Width w/ Amplifier	9" (228mm)	10-7/16" (265mm)
(D) Depth w/ grilles	11-1/8" (292mm)	13-3/16" (451mm)





INTENDED USE

- √ Recording Studios
- √ Bookshelf Speakers
- √ Home Theaters

OBJECTIVE

SPECIFICATIONS

Building on the legacy of the iQuake series the new StudioQuake line continues the quest to be thte best powered monitor speaker on the market today. With a focus honed on audio quality the StudioQuake features wideband ribbon tweeters, stiff aramid glass fiber woofers - powered by a high-end bi-amplification architecture giving each drive unit a dedicated amplifier.

Adhering to a stringent high performance, no-nonsense philosophy the StudioQuakes feature clean lines, smooth rounded corners and seamless magnetically attachable grilles. The dark graphite finish is elegant without being flashy. No gimmicky displays, blinking lights or novelty features. Just serious performance that leaves you free to produce or enjoy music.

SPECIAL FEATURES & HIGHLIGHTS

- · Balanced (XLR & TRS) and unbalanced (RCA) inputs
- 2- way powered monitor
- · 2" ultra fast ribbon tweeter
- Aramid glass fiber woofer
- HF level controls
- System volume control
- Rear ported design
- · Magnetically attached grilles
- · Sleek matte black finish

· · · · · · · · · · · · · · · · · · ·	otudio quake ino	otaaloguake Mo
Amplifier Power (HF/LF)	(105 Watts) 25W/80W	(125 Watts) 25W/100W
Frequency Range (-10 dB)	35Hz-40kHz	30Hz-40kHz
HF Driver	2" Ribbon Tweeter	
LF Driver	6.5" Aramid glass fiber	8" Aramid glass fiber

StudioQuake M6 StudioQuake M8

Black Matte

Finish