



Earthquake Sound Corporation
2727 McCone Ave., Hayward, Ca. 94545 USA
PH 510-732-1000 FX 510-732-1095
E-mail: tech@earthquakesound.com
Homepage: www.earthquakesound.com

ATTENTION: Valued Customer

Here are the instructions for you to change the amplifier on the Supernova MKV (old series) .

(Luminous 1000 or BA212 amplifiers.)

- 1- Disconnect the power and remove the power cord from the amplifier
- 2- Remove the passive radiator in order to allow yourself a lot of room to work. The passive radiator is the one with a bolt in the middle and it is not connected to anything.
- 3- Now, remove the perimeter screws on the amplifier metal plate, no other screws.
- 4- The amplifier plate should come out or you can push it from the inside.
- 5- Now disconnect the harnesses: two are coming from the transformer and one from the speaker.
- 6- Now, you need to remove the mounting screws of the transformer and install the new transformer. Make sure you use the same orientation. These harnesses are slightly different.
- 7- Once the transformer is installed review the amplifier instruction sheet in order to make sure that you connect one of the harnesses to **the 110 Volts side**. The speaker harness fit in one are and there is no polarity or orientation.
- 8- Screw the amplifier plate back in place.
- 9- I always recommend that the sub is tested a low power to make sure all is OK.
- 10- If all is good, then zip tie the long cables, so they do not flap against the wood when the sub is playing. Screw the passive back.

11- As always, we recommend that a tech perform this task.